

DuraRock Warrior

High-Quality Belting Created to Minimize the Effects of Abrasion and Absorb the Impact Caused by Rocks and Aggregates.



In your operations, you handle a significant volume of rugged materials like ore, aggregates, crushed stone, solid rocks, sand, and gravel. Your conveyor belting must not only be reliable and consistently efficient, but also tough enough to endure the severe operating conditions. These extreme conditions can cause your belting to suffer gouges, tears, rips, and abrasion, leading to premature failures, operational downtime, and increased maintenance costs.

That's where DuraRock Warrior comes in, designed with the premium abrasion and impact resistance you need.

Mitigate unforeseen downtime caused by belts failing prematurely or sudden emergencies. Cease reactive maintenance and embrace the assurance of uninterrupted operations with Warrior, providing consistent performance daily.

Explore DuraRock Warrior, a product from Duraline, supported by Viacore's expansive network featuring over 30 facilities and a team of 350 skilled conveyor service technicians.

Protect your operation using belting that offers a premium blend of the required strength and abrasion resistance.

Features and Benefits

Our DuraRock Warrior compound exceeds both ARPM Grade I and DIN W properties, offering a premium cover combination designed to provide high-end performance under severe impact loading, while still providing excellent abrasion resistance.

For additional properties and design considerations, please contact one of our Solutions Specialists.

DuraRock products are manufactured to Viacore's exacting standards. We control the specification, so that you get exactly what you need. You won't get a commodity product with properties determined by manufacturers out of touch with your requirements.



•**Tensile Strength:** Typical 2850 psi rubber tensile excellent for withstanding rock impact forces and loads, resisting gouging, ripping and tearing, allowing even longer belt life.

•**Abrasion Resistance:** Typical 80 mm³ din abrasion, offering excellent protection from the sliding abrasiveness of smaller rocks, sands and aggregates, resulting in superb service life of the cover and industry-low maintenance costs.

•**Elongation:** Typical 550% rubber elongation giving it the flexibility to absorb impact and last over time in the dry aggregate environment.

•**Temp. Range:** -40 to 200°F*: Warrior will operate in harsh conditions.

**200°F based on lumpy material on ambient air systems with sufficient cooling on return side. If the material is considered fines and/or the system is enclosed and/or the belt is not able to cool down on the return side, the maximum temperature will be reduced and/or the expected life of the belt will be reduced.*

Scan the QR code of visit www.Viacore.com/contact-us to contact one of our Solutions Specialists today. You'll get:



•**An ultra-responsive single-source partner** spanning across North America with a network of more than 30 locations, we ensure comprehensive coverage wherever your operations are situated.

•**Extensive inventory & fast delivery** to minimize your downtime.

•**Over 350 highly trained service technicians** that handle all your installation and maintenance services to keep you up and running.

•**Over 50 years of experience.** You'll have access to the deepest pool of knowledge in the industry, we've got the solution to every challenge you face.